Multilayer structures as stable hole-injecting electrodes for use in high efficiency organic electronic device

Publication number: CN1437773 Publication date: 2003-08-20

Inventor:

PARKER I D (US); CHI ZHANG (US) Applicant: DUPONT DISPLAY INC (US)

Classification:

- international: H05B33/26: H01L51/50: H01L51/52: H01L27/32-

H05B33/26; H01L51/50; H01L27/28; (IPC1-7):

H01L51/20: H01L27/00 - European: H01L51/50.1: H01L51/52B2


Application number: CN20018011439 20010618 Priority number(s): US20000212924P 20000620 Also published as:

WO0199207 (A3) WO0199207 (A2) EP1292996 (AO) CA2408321 (A1)

Report a data error here

Abstract not available for CN1437773 Abstract of corresponding document: WO0199207

Multilayer anode structures (104) for electronic devices (100) such as polymer light-emitting diodes are described. The multilayer anodes include a high conductivity organic layer (114) adjacent to the photoactive layer (102) and a low conductivity organic layer (112) between the high conductivity organic layer and the anode's electrical connection layer (110). This anode structure provides polymer light emitting diodes which exhibit high brightness, high efficiency and long operating lifetime. The multilaver anode structure of this invention provides sufficiently high resistivity to avoid cross- talk in passively addressed pixellated polymer emissive displays: the multilayer anode structure of this invention simultaneously provides long lifetime for pixellated polymer emissive displays.



Data supplied from the esp@cenet database - Worldwide

01811439.3 Page 1 of 2



□ 申请(专利)号: 01811439.3

凶 专利检索

□ 申请公开说明书 (38页)

申 请 号: 01811439.3 申 请 日: 2001.06.18

名 称: 作为稳定空穴-注入电极用于高效有机电子器件的多层结构

公开(公告)号: CN1437773 公开(公告)日: 2003.08.20

主 分 类 号: H01L51/20 分案原申请号:

分 类 号: H01L51/20;H01L27/00

颁证 日: 优先权: 2000.6.20 US 60/212.924

申请(专利权)人: 杜邦显示器股份有限公司

地 址: 美国加利福尼亚州

发明(设计)人: I·D·帕克;张驰 国际申请: PCT/US01/19482 2001.6.

国际公布: WO01/99207英2001.12.27 进入国家日期: 2002.12.19

专利 代理 机构: 中国专利代理(香港)有限公司 代理 人: 赵苏林:罗才希

檢要

本发明描述用于电子器件(100)如聚合物发光二极管的多层阳极结构(104)。该多层阳极包括一个与光活性层(102)邻接的高 (114)和一个介于高电导率有机层与阳极的电连接层(110)之间的低电导率层(112)。该阳极结构使聚合物发光二极管具有高元度 作寿命。本发明多层阳极结构的电阻率高到足以避免在无源导址象素化聚合物发光显示器中发生串扰;本发明的多层阳极结构 合物发光显示器具有长寿命。 01811439.3 Page 2 of 2



UNCHTEN/SHUBSTOCKOVEN COPERIGHT(C) STATE INTELLECTUAL PROPERTY OFFICE OF P.R.C. ALL RIGHTS RESERVED